

FORMETCO Tri-Face QuickPost Production Guide

General Information

The Formetco QuickPost Louver system requires extremely precise production standards in order to be successful. It is imperative that your final product is slit into the Graphic Louver sizes listed below. FORMETCO obtains this by slitting the printed PVC tile into individual Graphic Louvers using a custom-engineered slitting device.

Graphic Louver Width:	5 7/16"
Graphic Louver Spacing:	1/2"
Recommended Material:	15 oz. Rigid PVC



Production Process Overview

You will need the following information to accurately produce a QuickPost Face. You will need to know the dimensions of the FORMETCO QuickPost sign and the exact number of louvers. Use the formula below to assist with this calculation.

Use Inches as the Unit of Measure	
Total Printed Sign Height:	
Total Printed Sign Width:	
↓	
Total Print Height of Each Graphic Louver:	Formula Deduct 1" from Printed Sign Height) e.g. 14'-1" = 13' 11"
Total Number of Graphic Louvers:	Formula (Printed Sign Width ÷ 6") e.g. (48'x12) = 576" ÷ 6" = 96 Louvers

Slitting the Printed Sign into Graphic Louvers

Once you have printed the sign and confirmed dimensions you are prepared to cut the individual Graphic Louvers. Measure over the Graphic Louver width (5 7/16"), remove the Louver space of 1/2" and then repeat this process.



NOTE: If this process isn't done correctly text and images will appear stretched or distorted. Proper Louver slitting will deliver a high quality product.

